

AT SERIES VACUUM DRYING OVENS



AT SERIES: **SIZES FROM 0.9 TO 16 CUBIC FEET (25 TO 453L)**

DESKTOP MODELS

0.9 CU FT & 1.9 CU FT

Compact, powerful, precise.

AT09-UL



20 inches (50.8 cm)
Come included with 4 shelves. Can stack up to 8.

SHIPPING WEIGHT:
150 Lbs (68.03 kg)

AT19-UL



23 inches (58.4 cm)
Come included with 5 shelves. Can stack up to 10.

SHIPPING WEIGHT:
200 Lbs (90.7 kg)



MULTIZONE MODELS

3.2 CU FT & 7.5 CU FT

*Separate temperature controllers
connected to temperature detection
and heating elements in each shelf.*

AT32-UL



SHIPPING WEIGHT:
400 Lbs (181.4 kg)

AT75-UL



SHIPPING WEIGHT:
630 Lbs (283.8 kg)



MULTIZONE MODELS

16 CU FT

Vacuum ovens can boost production by drastically shortening drying times. Evaporation points are decreased by the application of the vacuum pressure, which hastens the removal of residual solvents and moisture / water content. This helps save time and energy, compared to other traditional oven applications.

AT160-UL



37 inches
(93.98 cm)

52 inches (132.1 cm)

33 inches (83.8 cm)



SHIPPING WEIGHT:
940 Lbs (426.4 kg)

SPECIFICATIONS

Model		AT09-UL	AT19-UL	AT32-UL	AT75-UL	AT160-UL
Electrical Requirements		110V, 50/60Hz, 1-PH / 220V, 50/60Hz 1-PH				
Power Output		1500 W / 1200 W	1500 W			
Environmental Operation Conditions		<ul style="list-style-type: none">• Indoor use and altitude up to 2000m• Temperature 5-40°C• Max. relative humidity 80% for temperatures up to 30°C decreasing linearly to 50 % relative humidity at 40°C• Mains supply volt fluctuations up to ±10 % of the nominal voltage• Transient overvoltage up to the levels of overvoltage category II (See Note 1).• Temporary overvoltage occurring on the mains supply.• Applicable pollution degree of the intended environment (pollution degree 2 inmost cases (See Note 2). <p>Note 1: These levels of transient overvoltage are typical for equipment supplied from the building wiring.</p> <p>Note 2: Manufacturers may specify more restricted environmental conditions for operation, nevertheless the equipment must be safe within these normal environmental conditions.</p>				
Chamber	Size (WxDxH)	12 x 12 x 11" (30.5 x 30.5 x 28 cm)	16.5 x 14.5 x 14" (42 x 36.8 x 35.6 cm)	18 x 18 x 18" (45.7 x 45.7 x 45.7 cm)	22 x 23.5 x 25" (55.9 x 59.7 x 63.5 cm)	25.6 x 30 x 35.5" (65 x 76.2 x 90.2 cm)
	Material	Stainless Steel				
	Capacity	0.9 cubic foot	1.9 cubic foot	3.2 cubic feet	7.5 cubic feet	16 cubic feet
Temperature Controller	Controller	3rd gen low proportional gain, microcomputer PID controlled with LCD display				
	Range	Ambient to 480°F (248°C)				Ambient to 200°F (100°C)
	Display Units	Fahrenheit or Celsius				
	Accuracy	±1				
	Uniformity	±5% of setpoint				
	Dwelling Time	1 to 9999 minutes				
	Warm up time to 100°F	40 minutes	45 minutes	35 minutes	45 minutes	55 minutes
Vacuum		Ultimate vacuum level: better than 500 microns/millitorrs (may vary based on your altitude) Mechanical vacuum gauge range: 0 to 30" mercury Mechanical vacuum gauge type: oil-filled Vacuum port: KF25 flange x 1 Vent port: KF25 flange x 1				
Door gasket material		Silicone (Standard), Viton (Optional)				
Observation window		1/2" tempered safety glass				
Shelves	Included with oven purchase	4 aluminum slide-in shelves	5 aluminum slide-in shelves	3 non-removable aluminum shelves	5 non-removable aluminum shelves	6 non-removable aluminum shelves
	Size (WxD)	11.5 x 11.25" (29.2 x 28.6 cm)	16 x 14.25" (40.6 x 36.2 cm)	17.5 x 17.25" (44.4 x 43.8 cm)	22 x 23.25" (55.9 x 59.1 cm)	25 x 29.25" (63.9 x 59.1 cm)
	Distance between shelves	1" (2.54 cm)		4.75" (12.1 cm)	2.25" (5.7 cm)	2.375" (6.03 cm)
In-door lights		White LED (pre-installed)				
Safety		Built-in circuit breaker, controller overheat protection, secondary over-temp protection dial				
Compliance		UL (E482564), CSA, CE				
Warranty		2 years				

FLOOR MODELS

5 CU FT & 7.5 CU FT

Large open chambers with fully removable shelves that are easy to clean. Perfect for large samples and applications like decarboxylation and drying solvent or moisture.

AT50x



Comes included with 7 shelves.Can stack up to 14.

AT75x



Comes included with 9 shelves.Can stack up to 18.



FLOOR MODELS

16 CU FT

Massive vacuum ovens for high production capacity.

AT160x



Comes included with 13 shelves. Can stack up to 26.



SHIPPING WEIGHT:
1200 Lbs. (544.3 kg)

SPECIFICATIONS

Model		AT50x	AT75x	AT160x
Electrical Requirements		110V, 50/60Hz, 1-PH / 220V, 50/60Hz 1-PH	220V +/- 10% 50/60Hz 1-PH	
Power Output		2600 W	3800 W	6000 W
Environmental Operation Conditions		<ul style="list-style-type: none"> Indoor use and altitude up to 2000m Temperature 5-40°C Max. relative humidity 80% for temperatures up to 30°C decreasing linearly to 50 % relative humidity at 40°C Mains supply volt fluctuations up to ±10 % of the nominal voltage Transient overvoltage up to the levels of overvoltage category II (See Note 1). Temporary overvoltage occurring on the mains supply. Applicable pollution degree of the intended environment (pollution degree 2 in most cases (See Note 2). <p>Note 1: These levels of transient overvoltage are typical for equipment supplied from the building wiring.</p> <p>Note 2: Manufacturers may specify more restricted environmental conditions for operation, nevertheless the equipment must be safe within these normal environmental conditions.</p>		
Chamber	Size (WxDxH)	19.75 x 21.5 x 19.75" (50.2 x 54.6 x 50.2 cm)	22 x 23.5 x 25" (55.9 x 59.7 x 63.5 cm)	25.6 x 30 x 35.5" (65.0 x 70.2 x 90.2 cm)
	Material	Stainless Steel		
	Capacity	5 cubic feet	7.5 cubic feet	16 cubic feet
Temperature Controller	Controller	3rd gen low proportional gain, microcomputer PID controlled with LCD display		
	Range	Ambient to 480°F (248°C)		
	Display Units	Fahrenheit or Celsius		
	Accuracy	±1		
	Uniformity	±5% of setpoint		
	Dwelling Time	1 to 9999 minutes		
	Warm up time to 100°F	45 minutes		40 minutes
Vacuum		Ultimate vacuum level: better than 500 microns/millitorrs (may vary based on your altitude) Mechanical vacuum gauge range: 0 to 30" mercury Mechanical vacuum gauge type: oil-filled Vacuum port: KF25 flange x 1 Vent port: KF25 flange x 1		
Door gasket material		Silicone		
Observation window		1/2" tempered safety glass		
Shelves	Included with oven purchase	7 aluminum pan-shaped shelves	9 aluminum pan-shaped shelves	13 aluminum pan-shaped shelves
	Size (WxD)	19.25 x 21 x 0.5" (48.89 x 53.34 x 1.3 cm)	21.75 x 23 x 0.5" (55.24 x 58.4 x 1.3 cm)	25 x 30" (63.9 x 76.2 cm)
	Distance between shelves	1" (2.54 cm)		
In-door lights		White LED (pre-installed)		
Safety		Built-in circuit breaker, controller overheat protection, secondary over-temp protection dial		
Compliance		UL (E482564), CSA, CE		

FLOOR MODELS

0.9 CU FT & 1.9 CU FT

More affordable and still made with the same quality you need and know! Perfect for smaller labs.

AT09e



Comes included with 4 shelves.Can stack up to 8.

AT19e



Comes included with 9 shelves.Can stack up to 18.

FLOOR MODELS

3.2 CU FT & 5.0 CU FT

ECO series Ai ovens are CE certified and come with a one year warranty, while our premier AT series UL/CSA/CE certified models come with a 2 year warranty.

AT32e

24 inches
(61 cm)

29 inches
(73.7 cm)

SHIPPING WEIGHT:
170 Lbs.(77.1 kg)

30.5 inches (77.5 cm)



AT50e

28 inches
(71.1 cm)

30 inches
(76.2 cm)

SHIPPING WEIGHT:
240 Lbs.(108.9 kg)

32.25 inches (81.92 cm)

Comes included with 7 shelves.Can stack up to 14.

SPECIFICATIONS

Model	AT09e	AT19e	AT32e	AT50e
Electrical Requirements	110V or 220V \pm 10%, 60Hz, 1-PH, 1,500 watts	110V \pm 10% 60Hz 1-PH 13.6A, 1,500 watts or 220V \pm 10% 50/60Hz 1-PH 6.8A, 1,500 watts		110V or 220V \pm 10% 50/60Hz 1-PH, 3,000 watts
Chamber	Size: 12 x 12 x 11" Material: Stainless steel Capacity: 0.9 cubic foot	Size: 16.5 x 14.5 x 14" Material: Stainless steel Capacity: 1.9 cubic foot	Size: 18 x 18 x 18" Material: Stainless steel Capacity: 3.2 cubic foot	Size: 19.75 x 21.5 x 19.75" Material: Stainless steel Capacity: 5.0 cubic foot
Heater	3-sided heating (left 400W, right 400W, bottom 700W)		500 watts x 3, built into 3 aluminum shelves	3-sided heating (left 800W, right 800W, bottom 1,400W)
Temperature control	Controller: 3rd gen low proportional gain, microcomputer PID controlled. Range: ambient to 250°C (or 480°F) Display units: Fahrenheit or Celsius Uniformity: \pm 5% of setpoint Dwelling timer range: 1 to 9999 mins. Warm-up time to 480°F: 80 minutes (Approx.)	Controller: 3rd gen low proportional gain, microcomputer PID controlled. Range: ambient to 250°C (or 480°F) Display units: Fahrenheit or Celsius Uniformity: \pm 5% of setpoint Dwelling timer range: 1 to 9999 mins. Warm-up time to 480°F: 90 minutes (Approx.)	Controller: 3rd gen low proportional gain, microcomputer PID controlled. Range: ambient to 250°C (or 480°F) Display units: Fahrenheit or Celsius Uniformity: \pm 5% of setpoint Dwelling timer range: 1 to 9999 mins. Warm-up time to 100°F: 35 mins 480°F: 60 mins.	Controller: low proportional gain, microcomputer PID controlled. Range: ambient to 250°C (or 480°F) Display units: Fahrenheit or Celsius Uniformity: \pm 7% of setpoint Dwelling timer range: 1 to 9999 mins.
Vacuum	Ultimate vacuum level: better than 500 microns/millitorrs Mechanical gauge range: 0 to 30 inch mercury Vacuum port: KF25 flange x 1 Vent port: 1/4" ball valve Vacuum pump: Sold separately			
Weight	Unit: 85 Lbs, shipping: 170 Lbs	Unit: 135 Lbs, shipping: 240 Lbs	Unit: 240 Lbs, shipping: 380 Lbs	Unit: 390 Lbs, shipping: 600 Lbs
Dimensions (WxDxH)	Unit: 23.4 x 17.25 x 19" With handle and vacuum port: 23.4 x 20 x 19"	Unit: 28 x 20 x 21.75" With handle and vacuum port: 28 x 23 x 21.75"	Unit: 30.5 x 24 x 29"	Unit: 32.25 x 28 x 30"
Shelves	Included with oven purchase: 4 aluminum slide-in shelf Capacity: 8 shelves max. Style: pan-shape Size: 11.5 x 11.25" Maximum area: 129.4 x 8 = 7 sq ft or 1,035 inch ² Distance between shelves: one inch	Included with oven purchase: 5 aluminum slide-in shelf Capacity: 10 shelves max. Style: pan-shape Size: 16 x 14.25" Maximum area: 228 x 10 = 16 sq ft or 2,280 inch ² Distance between shelves: one inch	Heated shelves: 3 non-removable aluminum shelves, 17.5 x 17.25" (WxD) each Optional stackable aluminum shelves: 17.5 x 17.25 x 2.25" (WxDxH) Total area without stackable shelves: 302 x 3 = 6 sq ft or 906 inch ² Total area with 3 stackable shelves: 302 x 6 = 12 sq ft or 1812 inch ² Distance between (without stackable shelves): 4.75 inches Distance between shelves (with 3 stackable shelves): 2.25 inches Max. load capacity per shelf: 20 Lbs	Included with oven purchase: 7 aluminum slide-in shelf Capacity: 14 shelves max. Style: pan-shape Size: 19.25 x 21 x 0.5" (WxDxH) Total area with 14 shelves: 39.3 sq ft or 5660 sq inch Distance between the most adjacent shelves: 1.25"
Door gasket material	Silicone (standard), Viton (optional)			
Observation window	1/2" tempered safety glass			
Safety	Built-in circuit breaker, Overheat shutoff protection			Built-in circuit breaker, Overheat shutoff protection Secondary over-temp protection dial
In-door lights	White LED			
Warranty	1 year			
Compliance	CE			N/A

ACCESSORIES

RECOMMENDED FOR PAIRING

VACUUM PUMPS



Vacuum Ovens	Ai	Edwards
AT09-UL	EasyVac 7 or SuperVac 5	nXDS6iC
AT19-UL	EasyVac 9 or SuperVac 5	nXDS6iC
AT32-UL	EasyVac 9 or SuperVac 11	RV8 or nXDS10iC
AT75-UL	SuperVac 11 or SuperVac 21	E2M28 or nXDS10iC
AT160-UL	SuperVac 21	E2M28 or nXDS20iC



Vacuum Ovens	Agilent	Welch	ULVAC	Vacuubrand
AT09-UL	IDP-3	2034	DTC-41	MD1CNT
AT19-UL	IDP-3	2052	UDP-6	MD4CNT
AT32-UL	IDP-7	2163	UDP-6	

COLD TRAPS

MOBILE CARTS



Vacuum REGULATORS



REPLACEMENT

PARTS

SHELVES

Vacuum Ovens	Flat Aluminium Shelves	Aluminium Pan Shelves
AT09-UL	SSA-09 (For old model ovens with brackets) SSA-09T (For new model ovens with brackets)	SSP-09
AT19-UL	SSA-19 (For old model ovens with brackets) SSA-19T (For new model ovens with brackets)	SSP-19
AT50x-UL	N/A	SSP-50
AT75x-UL	N/A	SSP-75
AT160x-UL	N/A	SSP-160



SSP-09



SSA-09



SSA-160

Floor Models	Stackable aluminum Shelves
AT32-UL	SSA-32
AT75-UL	SSA-75
AT160-UL	SSA-160

AUXILIARY ITEMS

Auxiliary Items	AT09-UL	AT19-UL	AT32-UL	AT75-UL	AT160-UL / AT160x
Food Grade Solvent-Resist Viton Gasket	N/A	OSG.AT.Viton-19	OSG.AT.Viton-32	OSG.AT.Viton-75	OSG.AT.Viton-160
High Temp Door Sealing Gasket	OSG.AT09	OSG.AT19	OSG.AT32	OSG.AT75	OSG.AT160
3rd Gen Low Gain LCD Controller	VO-570LPGTC-UL (except "ECO" series)				
Vacuum/Vent Valve Knobs	VO-VacVent-Knob				
Inch Mercury Vacuum Gauge	VO-INV6				
KF16 to KF25 Flange Adapter	KF16-25				
KF25 to KF40 Flange Adapter	KF25-40				
KF/NW16 Aluminum Wing Nut Flange Quick Clamp & Centering Ring	KF16.FCCR				
KF/NW25 Aluminum Wing Nut Flange Quick Clamp	KF25.FC				
Reinforced Door Handle	VOHe-09	VOHe-19	VOHe-32	VOHe-75	VOHe-160
Tempered Door Glass	VO.AT09	VO.AT19	VO.AT32	VO.AT75	VO.AT160



KF25.FC



38-T



FVB-25-10



KF-38-1



KF25-C



KF25-T

PACKAGES

DESKTOP MODELS

AT09-UL



Ai AT09-UL Vacuum Oven
Agilent IDP-3 Vacuum Pump
Ai T40x_UL Cold Trap

Alternative Pumps for the AT09-UL



Ai EasyVac 7



Ai SuperVac5-UL



Edwards nXDS6iC



ULVAC DTC-41



Welch 2034



Vacuubrand MD1CNT

AT19-UL



Ai AT19-UL Vacuum Oven
Agilent IDP-3 Vacuum Pump
Ai T40x_UL Cold Trap

Alternative Pumps for the AT19-UL



Ai EasyVac 9



Ai SuperVac5-UL



Edwards nXDS6iC



ULVAC DTC-41



Welch 2052



Vacuubrand MD4CNT

PACKAGES

FLOOR MODELS

AT50x



Ai AT50x Vacuum Oven
Agilent IDP-7 Vacuum Pump
Ai T40x-UL Cold Trap

Alternative Pumps for the AT50x



Ai EasyVac9



Ai SuperVac11-UL



Ai SuperVac21-UL



Edwards nXDS10iC



Edwards RV8



ULVAC UDP-6



Welch 2163



Agilent IDP-15

AT75x



Ai AT75-UL Vacuum Oven
Agilent IDP-15 Vacuum Pump
Ai T40x-UL Cold Trap

Alternative Pumps for the AT75x



Ai SuperVac11-UL



Ai SuperVac21-UL



Edwards nXDS10iC



Edwards nXDS10iC



Edwards E2M28

PACKAGES

FLOOR MODELS

AT160x



Ai AT160x Vacuum Oven
Edwards nXDS20iC
Vacuum Pump
Ai T40x-UL Cold Trap

Alternative Pumps for the AT160x



Ai SuperVac21-UL



Edwards E2M28



Welch CRVPro30

PACKAGES

MULTIZONE MODELS

AT32-UL



Ai AT32-UL Vacuum Oven
Agilent IDP-7 Vacuum Pump
Ai T40x-UL Cold Trap

Alternative Pumps for the AT32-UL



Ai EasyVac9



Ai SuperVac11-UL



Edwards RV8



Edwards nXDS10iC



Welch 2163



ULVAC UDP-6

AT75-UL



Ai AT75-UL Vacuum Oven
Agilent IDP-15 Vacuum Pump
Ai T40x-UL Cold Trap

Alternative Pumps for the AT75-UL



Ai SuperVac11-UL



Ai SuperVac21-UL



Edwards nXDS10iC



Edwards E2M28



Welch CRVPro 16

PACKAGES

MULTIZONE MODELS

AT160-UL



Ai AT160-UL Vacuum Oven
Edwards nXDS20iC Vacuum Pump
Ai T40x-UL Cold Trap



Alternative Pumps for the AT160-UL



Ai SuperVac21-UL



Edwards E2M28



Welch CRVPro30

STACKABLE PACKAGES

NEW

0.9 Cu Ft Vacuum Ovens *Mobile Cart Package*



Digital Vacuum Gauge
Option Available



T80x Cold Trap
Upgrade Available



Compatible Vacuum Pumps	
Ai	SVC5 (UL,CSA,CE Compliant to 110v models)
Agilent	IDP-7
Edwards	nXDS6ic
ULVAC	UDP-6
Welch	CRVPro8, 2052 (Only 110V models are UL, CSA)

Floor Space	
Length	60 in
Width	36 in
Height	82 in
Weight	686 lb



STACKABLE PACKAGES

NEW

0.9 Cu Ft Vacuum Ovens *Mobile Cart Package*

Digital Vacuum Gauge
Option Available



MC19-3 - Cart

T40x

T40x

MC19-3 - Cart

T80x Cold Trap
Upgrade Available

Compatible Vacuum Pumps

Ai	SVC11 (UL,CSA,CE Compliant to 110v models)
Agilent	IDP-15
Edwards	nXDS10ic
ULVAC	UDP-6
Welch	CRVPro8, 2163 (Only 110V models are UL, CSA)

Floor Space

Length	112 in
Width	36 in
Height	82 in
Weight	1086 lb



STACKABLE PACKAGES

NEW

1.9 Cu Ft Vacuum Ovens *Mobile Cart Package*



Digital Vacuum Gauge
Option Available



T80x Cold Trap
Upgrade Available



Compatible Vacuum Pumps	
<i>Ai</i>	<i>SVC11</i> (UL,CSA,CE Compliant to 110v models)
<i>Agilent</i>	<i>IDP-15</i>
<i>Edwards</i>	<i>nXDS10ic</i>
<i>ULVAC</i>	<i>UDP-6</i>
<i>Welch</i>	<i>CRVPro8, 2163</i> (Only 110V models are UL, CSA)

Floor Space	
<i>Length</i>	<i>60 in</i>
<i>Width</i>	<i>36 in</i>
<i>Height</i>	<i>84 in</i>
<i>Weight</i>	<i>1086 lb</i>



STACKABLE PACKAGES

NEW

1.9 Cu Ft Vacuum Ovens *Mobile Cart Package*



Compatible Vacuum Pumps

Ai	SVC21 (UL,CSA,CE Compliant to 110v models)
Edwards	nXDS20ic, E2M28
Welch	CRVPro30

Floor Space

Length	118 in
Width	36 in
Height	84 in
Weight	1386 lb



3.2 Cu Ft Vacuum Ovens *Mobile Cart Package*



Digital Vacuum Gauge
Option Available



T80x Cold Trap
Upgrade Available



Compatible Vacuum Pumps

Ai	SVC11 (UL,CSA,CE Compliant to 110v models)
Agilent	IDP-15
Edwards	nXDS10ic, RV8
Welch	2163 (Only 110V models are UL, CSA)

Floor Space

Length	63 in
Width	40 in
Height	67 in
Weight	1000 lb

3.2 Cu Ft Vacuum Ovens *Mobile Cart Package*

Digital Vacuum Gauge
Option Available



AT32
MC32 - Cart

T40x

T40x

MC32 - Cart

T80x Cold Trap
Upgrade Available

Compatible Vacuum Pumps

Ai	SVC21 (UL,CSA,CE Compliant to 110v models)
Edwards	nXDS20ic
Welch	CRVPro16, CRVPro30

Floor Space

Length	118 in
Width	40 in
Height	67 in
Weight	1650 lb

STACKABLE PACKAGES

NEW

5.0 Cu Ft Vacuum Ovens *Mobile Cart Package*



**Digital Vacuum Gauge
Option Available**



**T80x Cold Trap
Upgrade Available**



Compatible Vacuum Pumps

Ai	SVC11 (UL,CSA,CE Compliant to 110v models)
Edwards	nXDS20ic
Welch	CRVPro16

Floor Space

Length	67 in
Width	46 in
Height	81.5 in
Weight	1310 lb



STACKABLE PACKAGES

NEW

5.0 Cu Ft Vacuum Ovens *Mobile Cart Package*

Digital Vacuum Gauge
Option Available



Compatible Vacuum Pumps

Ai	SVC21 (UL,CSA,CE Compliant to 110v models)
Edwards	E2M28
Welch	CRVPro48, CRVPro30

Floor Space

Length	126 in
Width	46 in
Height	81.5 in
Weight	2260 lb



STACKABLE PACKAGES

NEW

7.5 Cu Ft Vacuum Ovens *Mobile Cart Package*



Digital Vacuum Gauge
Option Available



T80x Cold Trap
Upgrade Available



Compatible Vacuum Pumps

Ai	SVC21 (UL,CSA,CE Compliant to 110v models)
Edwards	E2M28
Welch	CRVPro48, CRVPro30

Floor Space

Length	67 in
Width	46 in
Height	84 in
Weight	1390 lb



STACKABLE PACKAGES

NEW

7.5 Cu Ft Vacuum Ovens *Mobile Cart Package*

Digital Vacuum Gauge
Option Available



CRVPro48



AT75a
MC75- Cart

T40x

T80x Cold Trap
Upgrade Available

T40x

AT75a
MC75- Cart

Compatible Vacuum Pumps

Welch

CRVPro48

Floor Space

Length	126 in
Width	46 in
Height	84 in
Weight	2420 lb



STACKABLE PACKAGES

NEW

7.5 Cu Ft Vacuum Ovens *Mobile Cart Package*



Digital Vacuum Gauge
Option Available



T80x Cold Trap
Upgrade Available



Compatible Vacuum Pumps

Ai	SVC21 (UL,CSA,CE Compliant to 110v models)
Edwards	E2M28
Welch	CRVPro48, CRVPro30

Floor Space

Length	67 in
Width	46 in
Height	84 in
Weight	1390 lb



STACKABLE PACKAGES

NEW

7.5 Cu Ft Vacuum Ovens *Mobile Cart Package*

Digital Vacuum Gauge
Option Available



CRVPro48



Compatible Vacuum Pumps

Welch

CRVPro48

Floor Space

Length	126 in
Width	46 in
Height	84 in
Weight	2420 lb



CONTACTS

& SUPPORT

NEW JERSEY

*111 Dorsa Avenue
Livingston, NJ, 07039
USA*

NEVADA

*600 Spice Island Dr.
Sparks, NV, 89431
USA*

*Tel: 888-988-0899
info@acrossinternational.com
quotes@acrossinternational.com*

Website: www.acrossinternational.com

*For Technical Support:
support@acrossinternational.com*

